



VEJSIKRING

**Anti-nudge hoop 90°
equal-sided**

Steel tube \varnothing 76 mm
hot-dip galvanized and coated
yellow with black stripes



Stationary, for casting in concrete



Total width	Height above ground	Approx.kg	Part-No.
350 mm	650 mm	19.0	477.30BG
350 mm	1150 mm	25.0	477.31BG
600 mm	650 mm	22.0	477.60BG
600 mm	1150 mm	27.5	477.61BG

For plugging down

350 mm	650 mm	13.5	477.30PBG
350 mm	1150 mm	21.0	477.31PBG
600 mm	650 mm	16.0	477.60PBG
600 mm	1150 mm	24.0	477.61PBG

**Anti-nudge hoop
Double hoop**

Steel tube \varnothing 76 mm
hot-dip galvanized and coated
yellow with black stripes

Stationary, for casting in concrete



Total width	Total depth	Height above ground	Approx.kg	Part-No.
750 mm	450 mm	650 mm	28.5	477.68BG
750 mm	450 mm	1150 mm	36.0	477.69BG
1000 mm	450 mm	650 mm	30.0	477.70BG
1000 mm	450 mm	1150 mm	37.5	477.71BG

For plugging down



750 mm	450 mm	650 mm	21.0	477.68PBG
750 mm	450 mm	1150 mm	31.5	477.69PBG
1000 mm	450 mm	650 mm	22.0	477.70PBG
1000 mm	450 mm	1150 mm	32.5	477.71PBG

Anti-nudge hoop 90°

One sided, deep version

Steel tube Ø 76 mm

hot-dip galvanized, powder-coated yellow, with black warning stripes



	Total width	Total depth	Height above ground	Approx.kg	Part-No.
Stationary, for casting in concrete					
One side, right					
	600 mm	350 mm	650 mm	13.5	477.76BG
	600 mm	350 mm	1150 mm	17.0	477.77BG
For plugging down					
One side, right					
	600 mm	350 mm	650 mm	10.0	477.76PBG
	600 mm	350 mm	1150 mm	15.0	477.77PBG



	Total width	Total depth	Height above ground	Approx.kg	Part-No.
Stationary, for casting in concrete					
One side, left					
	600 mm	350 mm	650 mm	13.5	477.78BG
	600 mm	350 mm	1150 mm	17.0	477.79BG
For plugging down					
One side, left					
	600 mm	350 mm	650 mm	10.0	477.78PBG
	600 mm	350 mm	1150 mm	15.0	477.79PBG

Anti-nudge hoop

double-sided, deep version

Steel tube Ø 76 mm

hot-dip galvanized and coated yellow with black stripes



	Total width	Total depth	Height above ground	Approx.kg	Part-No.
Stationary, for casting in concrete					
	750 mm	450 mm	650 mm	17.0	477.72BG
	1000 mm	450 mm	650 mm	18.0	477.73BG
	750 mm	450 mm	1150 mm	20.0	477.74BG
	1000 mm	450 mm	1150 mm	21.0	477.75BG
For plugging down					
	750 mm	450 mm	650 mm	13.0	477.72PBG
	1000 mm	450 mm	650 mm	14.0	477.73PBG
	750 mm	450 mm	1150 mm	18.0	477.74PBG
	1000 mm	450 mm	1150 mm	19.0	477.75PBG



Safety protection for posts, pillars, poles, etc.

Anti-nudge hoop for posts

steel tube construction with 2 hoops \varnothing 60 mm with welded-on cross-bars for nesting for plugging down, with base plates 100 x 150 mm, hot-dip galvanized, powder-coated yellow, with black warning stripes



For plugging down

Total width	Total depth	Height above ground	Approx.kg	Part-No.
600 mm	600 mm	650 mm	19.0	465.066PBG
800 mm	800 mm	800 mm	24.0	465.068PBG

Also available in hot-dip galvanized and white / red !



Other color finishes possible;



Crash guard with underrun guard

prevents underrunning of platform floor trucks and protects from fork trucks



Protection hoops, Steel tube \varnothing 76 mm

for plugging down, with base plates 100 x 150 mm, hot-dip galvanized, powder-coated yellow, with black warning stripes

For plugging down

Total width	Height above ground	Approx.kg	Part-No.
750 mm	650 mm	17.0	477.32BG
1000 mm	650 mm	21.0	477.33BG